



MOLYFLEX-6

Description

Molyflex-6 is an outstanding heat stable, long life fully synthetic non-melting grease. It is superior for high temperature application such as conveyors-tenters-electric motor-oven-applications-high temperature processing equipments. Contains molybdenum disulfide as solid lubricant. The moly additive is greatly responsible for superior performance by reducing friction and heat. The protective film formed by molybdenum disulfide prevents metal to metal contact even if the base lubricant should get squeezed out.

Operational Benefits

- * Excellent thermal and oxidation stability, longest life.
- * Good waterproof characteristic.
- * High load carrying ability.
- * Will not form carbon, sludge or varnish within useful temperature range.
- * Non-melting dropping point over 260°C.
- * Contains no petroleum or silicone components.

Technical Data

<u>Characteristic</u>	<u>Value</u>
Penetration (Worked)	265 – 295
NLGI Number	2
Dropping Point, °C	Non Drop
Operating Temperature	Continuous –54 to 200 Intermittent 260

Must not be mixed with conventional soap based greases

SLOAN INTERNATIONAL INC.

NEW BURGH, N.Y. 12550
U.S.A.

This information and recommendations of this product are based upon laboratory tests and experience and to the best of our knowledge and belief are true and accurate. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty or implied.



K K Traders Pakistan

Our products makes your equipment better!

faraz@kktraderspakistan.com
www.KKTradersPakistan.com