



SYNTHOLUBE-22 EP

Description

Syntholube-22 EP Grease is advanced Industrial grease made from synthetic hydrocarbon fluid, non-soap thickeners/ antiwear additives and antioxidants, It gives outstanding low torque, long lubricant life, in addition it provides high load carrying ability and corrosion protection for a wide temperature rang of surface.

Operational Benefits

- * Excellent thermal and oxidation stability, longest life.
- * Good waterproof characteristic.
- * High load carrying ability.
- * Will not form carbon, sludge or varnish within useful temperature range.
- * Non-melting dropping point over 260°C.
- * Contains no petroleum or silicone components.

Technical Data

<u>Characteristic</u>	<u>Value</u>	<u>Method</u>
Color		Brown
Worked Penetration at 25 deg °C	265 - 295	ASTM D-217
Drop Point, deg °C, min	260	ASTM D-566
Service Temperature, deg °C,	-30 to 180	

SLOAN INTERNATIONAL INC.

NEW BURGH, N.Y. 12550
U.S.A.

This information and recommendations of this product are based upon laboratory tests and experience and to the best of our knowledge and belief are true and accurate. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty or implied.



K K Traders Pakistan

Our products makes your equipment better!

faraz@kktraderspakistan.com
www.KKTradersPakistan.com