



AVILITH GREASE HV

Description

Sloan Avilith Grease HV is an advance grease made from highly refined petroleum oil of high viscosity, extreme pressure/antiwear additives and antioxidants. It gives outstanding low torque, long lubricant life. In addition it provides high load carrying ability and corrosion protection for a wide temperature range of service.

Operational Benefit

- * Reduces maintenance costs due to excellent film strength and adhesion quality.
- * It is intended for the lubrication of heavily loaded sliding surfaces or for antifriction bearings.

Technical Data

<u>Characteristic</u>	<u>Unit</u>	<u>Value</u>	<u>Test Methods</u>
Dropping point	°C	≥ 245	ASTM D 566
Penetration Unworked	1/10 mm	280	ASTM D 217
NLGI No.		2	
Kinematic Viscosity Index			ASTM D 445
@ 40 °C	cSt	170	
@ 100 °C	cSt	15	
Bearing test at 149°C	h	860	FTM-S-791 Method 331
Copper corrosion 24 h at 100 °C	-	1a	AIR 1650

Must not be mixed with conventional soap based grease

SLOAN INTERNATIONAL INC.

NEW BURGH, N.Y. 12550
U.S.A.

This information and recommendations of this product are based upon laboratory tests and experience and to the best of our knowledge and belief are true and accurate. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty or implied.



K K Traders Pakistan

Our products makes your equipment better!

faraz@kktraderspakistan.com
www.KKTradersPakistan.com