



LITHOPLEX LG 700

Description

Lithoplex LG 700 is a multipurpose industrial fluid grease containing EP additives, and rust and oxidation and inhibitors.

Operational Benefits

- * Protect bearing subject heavy or shock load conditions
- * Resists water wash out and helps protect bearing from rusting
- * Can be used at varying temperatures under wet or dry conditions
- * Suitable for use in centralized lubrication systems

Applications

Recommended for use in enclosed filled-for-life gear boxes where the use of a fluid lubricant is required. Suitable for rolling bearings, plain bearings, guides, spindles, machine tools as well as in assembly and conveyer systems.

Technical Data

<u>Characteristic</u>	<u>Value</u>
Color	Brown
Operating Temperature °C	-30 to 270
Dropping point °C	180
Penetration, worked at 25 °C	700
Timken OK load, Kg	18
Kinematic viscosity of oil at 40 °C	110

SLOAN INTERNATIONAL INC.

NEW BURGH, N.Y. 12550
U.S.A.

This information and recommendations of this product are based upon laboratory tests and experience and to the best of our knowledge and belief are true and accurate. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty or implied.



K K Traders Pakistan

Our products makes your equipment better!

faraz@kktraderspakistan.com
www.KKTradersPakistan.com