



SYNTHOLUBE-90

Description

Syntholube-90 is super quality synthetic gear lubricant, with honey like consistency and high adhesive properties, especially designed to meet the needs of all bearing surface and precision equipment, where high demands are is a very long service life is required.

Syntholube-90 is intended for rolling and plain bearings, sintered metal bearings, drying cylinders, sizing dryers, calendaring machines, hydrostatic gears etc.

Operational Benefits

- * Possess excellent protection against rust corrosion and oxidation
- * Having high load carrying capacity
- * High viscosity index high thermal stability, high flash point & low volatility
- * Suitable for continuous temperature upto 300°F, intermittent 400°F.

Technical Data

<u>Characteristic</u>	<u>Value</u>	<u>Method</u>
Viscosity cSt		ASTM D-445
100°C	16.0	
40°C	112.0	
Viscosity Index	146	ASTM D-2270
Pour Point, °C	-40	ASTM D-97
Flash point, °C	200	ASTM D-92

SLOAN INTERNATIONAL INC.

NEW BURGH, N.Y. 12550
U.S.A.

This information and recommendations of this product are based upon laboratory tests and experience and to the best of our knowledge and belief are true and accurate. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty or implied.