



BENTOP HV GREASE

Description

Bentop HV Grease is advance grease made from highly refined ISO VG 220 mineral oil, extreme pressure/antiwear additives and antioxidants. It gives outstanding low torque, long lubricant life. In addition it provides high load carrying ability and corrosion protection for a wide temperature range of service.

Operational Benefit

- * It is intended for the lubrication of automotive and industrial anti-friction bearings and chassis components.
- * Also recommended for normal-temperature application where resistance to water wash-out is required.
- * Maximum operation temperature of 175°C.

Technical Data

<u>Properties</u>	<u>Units</u>	<u>Typical Value</u>	<u>Test Methods</u>
- Appearance	-	homogeneous paste	-
- Colour	-	Dark Blue	-
- Dropping point	°C	≥ 240	ASTM D 566
- Penetration	1/10 mm		ASTM D 217
- Unworked		270	
- 60 strokes		274	
- Oil separation 30 h at 100 °C	% weight	2.0	AIR 1650
- Bearing test at 149°C	h	860	FTM-S-791 method 331
- Copper corrosion 24 h at 100 °C	-	1a	AIR 1650

Must not be mixed with conventional soap based greases

SLOAN INTERNATIONAL INC.

NEW BURGH, N.Y. 12550
U.S.A.

This information and recommendations of this product are based upon laboratory tests and experience and to the best of our knowledge and belief are true and accurate. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty or implied.



K K Traders Pakistan

Our products makes your equipment better!

faraz@kktraderspakistan.com
www.KKTradersPakistan.com