



FG-40

Food Grade Oil

Description

FG-40 the Food Grade Multi-Purpose Oil have been formulated to fulfill the requirements of both Multi-Purpose Lubrication in all plants. This oil possesses anti-wear, anti-rust, antifoam, and anti-oxidation additives, along with a selected EP package.

FG-40 oil are used in central and circulating lubrication system, drip cups, oil cans, oil reservoirs, and all types of manual applications. They satisfy anti-wear demands, and rust and oxidation provision for all types of equipment where a non-toxic lubricant is recommended or dictated!

Operational Benefits

- * Extended part life
- * Superior oxidation resistance
- * Excellent water separation properties
- * Water clear color

Technical Data

<u>ISOVG Grade</u>	<u>32</u>	<u>46</u>	<u>68</u>	<u>100</u>
Visosity				
cSt@ 40 °C	30.1	45	67	108
cSt@ 100 °C	5.2	6.8	8.9	12.3
cSt@ 100 °F	142	209	310	500
cSt@ 210 °F	43	48	55	67
Viscosity Index	102	105	105	105
Flash point COC °F/°C	390/199	390/199	394/201	394/201
Pour point °F/°C	-30/-34	-30/-34	-25/-32	-25/-32

SLOAN INTERNATIONAL INC.

NEW BURGH, N.Y. 12550
U.S.A.

This information and recommendations of this product are based upon laboratory tests and experience and to the best of our knowledge and belief are true and accurate. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty or implied.



K K Traders Pakistan

Our products makes your equipment better!

faraz@kktraderspakistan.com
www.KKTradersPakistan.com