



Description

HTL Plus is synthetic base high temperature lubricating oil designed for use applications upto 450 °F. It offers superior lubrication for high temperature ovens chains conveyors and various bearings exposed to harsh environmental conditions. Contains Molybdenum Disulfide that will continue to give lubrication upto 750 °F in the absence of base fluid.

Operational Benefits

- * Fully Synthetic
- * Highest degree of oxidation and thermal stability: will not form carbon, gum or sludge deposits.
- * Low evaporation rate – lasts longer
- * High Load carrying capacity
- * Contains Molybdenum Disulfide for added wear protection

Technical Data

<u>Characteristic</u>	<u>Method</u>	<u>Value</u>
Viscosity (Base Fluid)		
210°F cSt	ASTM D-445	26.6
100°F cSt	ASTM D-445	281
Viscosity Index	ASTM D-2270	124
Pour Point °F	ASTM D-97	0
Flash Point °F	ASTM D-92	510
Fire Point °F	ASTM D-92	600
Specific Gravity 60/60°F	ASTM D-1298	0.942

SLOAN INTERNATIONAL INC.

NEW BURGH, N.Y. 12550
U.S.A.

This information and recommendations of this product are based upon laboratory tests and experience and to the best of our knowledge and belief are true and accurate. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty or implied.



K K Traders Pakistan
Our products makes your equipment better!

faraz@kktraderspakistan.com
www.KKTradersPakistan.com