



HYDROSUPER

ISO VISCOSITY GRADES: 32- 46 – 68 – 100

Description

Hydrosuper is Microfiltered premium quality hydraulic oil with multi-metal compatibility. Hydrosuper is made from solvent refined high viscosity index base stock combined with anti-wear, defoamant additives and rust inhibitors, to give highly stable premium anti-wear hydraulic fluids with quality reserve for excellent performance under severe operation conditions and extended drains.

Operational Benefits

- * Longer hydraulic / machine components life
- * Cleaner servo valves, less chances of sticking
- * Superior oxidation and hydrolytic stability
- * Multi-metal compatibility under wet and dry condition
- * Superior protection in contaminated conditions of water and dirt
- * Long fluid life
- * Superior filterability increases filter life

Applications

Hydrosuper is recommended for all mobile and stationary hydraulic systems operating under the most severe conditions. Hydrosuper can also be used in circulation, splash and ring oil lubrication systems and compressors where recommended.

Technical Data

<u>Characteristic</u>	<u>Value</u>				<u>Method</u>
	<u>32</u>	<u>46</u>	<u>68</u>	<u>100</u>	
Appearance	Clear Liquid	Clear Liquid	Clear Liquid	Clear Liquid	Visual
Viscosity, cSt					ASTM D-445
@ 100°C	6.3	6.8	8.5	11.4	
@ 40°C	32.1	44	66.5	99.5	
Pour Point, °C	-12	-12	-9	-6	ASTM D-97
Flash Point COC, °C	178	220	228	232	ASTM D-93
Acid Number mg KOH/g	0.6	0.6	0.6	0.6	ASTM D-664

SLOAN INTERNATIONAL INC.

NEW BURGH, N.Y. 12550
U.S.A.

This information and recommendations of this product are based upon laboratory tests and experience and to the best of our knowledge and belief are true and accurate. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty or implied.



K K Traders Pakistan

Our products makes your equipment better!

faraz@kktraderspakistan.com
www.KKTradersPakistan.com