



MOLYGUARD HT

Description

MOLYGUARD HT is an extreme pressure, high temperature, lubricating compound with high adhesive properties. Suitable for both open gears, plain rolling bearings.

MOLYGUARD HT is based on pure aliphatic hydrocarbon polymers which have particular properties as base oils and modifiers to improve the performance of industrial grease, also contains extreme pressure additives, antioxidant and is reinforced by the addition of highly purified micronised Molybdenum Disulfide.

Operational Benefits

- * Non-Drop, Non-Melt, Non-Carbonising even at high temperature
- * High adhesive properties
- * Long-term lubrication
- * Excellent load carrying
- * Inhibits oxidation, thus ensuring protection against corrosion
- * Water repellent and resistant to salt water atmosphere, alkalis and acids

Technical Data

<u>Characteristic</u>	<u>Value</u>
Color	Metallic Black
Drop point	None
Consistency class	NLGI 2
Service temperature	-10 to 300°C

Must not be mixed with conventional soap based greases

SLOAN INTERNATIONAL INC.

NEW BURGH, N.Y. 12550
U.S.A.

This information and recommendations of this product are based upon laboratory tests and experience and to the best of our knowledge and belief are true and accurate. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty or implied.



KK Traders Pakistan

Our products makes your equipment better!

faraz@kktraderspakistan.com
www.KKTradersPakistan.com