



## MOLYTOP ND GREASE

### Description

Molytop ND Grease is manufactured from solvent refined mineral oil, extreme pressure additive, anti-oxidant-thickened with modified bentonite and reinforced by the addition of highly purified micronised Molybdenum Disulfide.

Molytop ND Grease is recommended for applications where the grease is required to support heavy load and high temperature upto 190°C under continuous operating conditions as high as 260°C for limited period.

### Operational Benefits

- \* Non-Drop, Non-Melt even at high temperature.
- \* Excellent load carrying characteristics.
- \* Resists softening under conditions of high speed.
- \* Inhibit oxidation, thus ensuring protection against corrosion.
- \* Contains micronised molybdenum disulfide that helps to prevent damage after the base grease is wiped off.

### Technical Data

<u>Characteristic</u>	<u>Value</u>
Color	Metallic Black
Worked Penetration at 25°C	220-250 (ASTM D-217)
Service Temperature	-12°C to 190°C
Drop Point	None

Must not be mixed with conventional soap based greases

**SLOAN INTERNATIONAL INC.**  
NEW BURG, N.Y. 12550  
U.S.A.

This information and recommendations of this product are based upon laboratory tests and experience and to the best of our knowledge and belief are true and accurate. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty or implied.



**K K Traders Pakistan**

Our products makes your equipment better!

faraz@kktraderspakistan.com  
www.KKTradersPakistan.com