SYNTHOLUBE-07 EP

Description

Syntholube-07 EP Grease is based on synthetic oil having viscosity 5 cSt at 100°C.

It is intended for use over the temperature range of -40°C to +177°C to lubricate antifriction bearings operating at high or low temperatures or when long detention and water resistance is desired.

Technical Data

Properties	Units	Typical Values	Test Methods
Appearance	-	caramel coloured paste	-
Dropping Point	°C	308	ASTM D 566
Penetration	1/10 mm		ASTM D 217
unworked		272	
after 60 strokes		280	
Mean hertz load	daN	49.4	ASTM D 2596
M.R.C. Bearing test at 177°C	h	589	FTM-S-791 method 331
Oil separation 30 h at 100°C	% weight	3.7	FTM-S-791 Method 321

Must not be mixed with conventional soap based greases

SLOAN INTERNATIONAL INC.
NEW BURGH, N.Y. 12550
U.S.A.

This information and recommendations of this product are based upon laboratory tests and experience and to the best of our knowledge and belief are true and accurate. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty or implied.

K K Traders Pakistan
Our products makes your equipment better!
faraz@kktraderspakistan.com
www.KKTradersPakistan.com