



SYNTHOLUBE-22 FLUID

Description

Syntholube-22 is super quality synthetic lubricant fluid, especially designed to meet the needs of all-bearing surface and precision equipment, where high demands are to be met and a very long service life is required.

Syntholube-22 is intended for rolling and plain bearings, sintered metal bearings, electronic and telecommunication equipments, precision measuring instruments, etc.

Operational Benefits

- * Formulated for long lasting lubrication
- * Possess excellent protection against rust corrosion and oxidation
- * Having high load carrying capacity
- * High viscosity index high thermal stability, high flash point & low volatility
- * Suitable for continuous temperature upto 300°F, intermittent 400°F.

Technical Data

<u>Characteristic</u>	<u>Value</u>	<u>Method</u>
Viscosity cSt		ASTM D-445
210°F	5.0	
100°F	26.5	
Viscosity Index	150	ASTM D-2270
SEA viscosity grade	5W	SAE J 309a
Pour Point, °F	-85	ASTM D-97
Flash point, °F	480	ASTM D-92
Fire point, °F	550	ASTM D-92
Autoignition temperature °F	740	ASTM D-2155
Conradson carbon, %	0.06	ASTM D-189
Evaporation, 22hur @ 210°F, %	0.20	ASTM D-972
Specific gravity, 60/60 °F	0.987	ASTM D-1298
API gravity	11.9	ASTM D-287
Density, lbs/gal, 60°F	8.24	

SLOAN INTERNATIONAL INC.

NEW BURGH, N.Y. 12550
U.S.A.

This information and recommendations of this product are based upon laboratory tests and experience and to the best of our knowledge and belief are true and accurate. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty or implied.



K K Traders Pakistan

Our products makes your equipment better!

faraz@kktraderspakistan.com
www.KKTradersPakistan.com