



## ULTRALUBE-170

### Description

Ultralube-170 synthetic compressor lubricant is based on premium quality synthesized base stock and selective additive technology. It is designed to satisfy the lubrication requirements of the majority of compressor in service today.

### Operational Benefits

- \* Extended drain interval
- \* Reduced maintenance costs
- \* Less oil consumption
- \* Reduced varnish, sludge and carbon deposits
- \* Fewer air filter changes
- \* Extended oil separator service intervals
- \* Reduced component wear
- \* Improved compressor efficiency
- \* Less downtime
- \* Superior lubricant oxidation and thermal stability

### Technical Data

<u>Characteristic</u>	<u>Value</u>
ISO viscosity grade	170
Kinematic Viscosity, (ASTM D445)	
@ 40°C cSt.	175
@ 100°C cSt.	16.5
Viscosity Index (ASTM D2270)	93
Density 15 °C g/ml (ASTM D4052)	0.96
Flash Point, °C (PMCC) (ASTM D92)	265
Pour Point, °C (ASTM D97)	-22
Specific Gravity g/ml (ASTM D4052)	0.96

**SLOAN INTERNATIONAL CORP.**

U.S.A.

This information and recommendations of this product are based upon laboratory tests and experience and to the best of our knowledge and belief are true and accurate. Since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty or implied.